

Material Safety Data Sheet
 May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910.1200. Standard must be
 consulted for specific requirements.

U.S. Department of Labor
 Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072



IDENTITY (As Used on Label and List)

STICKY WAX - RED

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name National Keystone Products Company	Emergency Telephone Number (800) 535-5053
Address (Number, Street, City, State, and ZIP Code) 616 Hollywood Avenue	Telephone Number for Information 856-663-4700
Cherry Hill, NJ 08002	Date Prepared July 2002 Reviewed July 2006
	Signature of Preparer (optional) M.P.

Section II — Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
N/A Natural waxes / pine resin				

Section III — Physical/Chemical Characteristics

Boiling Point	400	Specific Gravity (H ₂ O = 1) @ 25 C	0.982
Vapor Pressure (mm Hg.)	N/A	Melting Point	70 C
Vapor Density (AIR = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	N/A
Solubility in Water	No		
Appearance and Odor	Red color, hard wax, pine pitch odor		

Section IV — Fire and Explosion Hazard Data

Flash Point (Method Used) 465 F Open cup method	Flammable Limits N/A	LEL	UEL
Extinguishing Media Dry chemical			
Special Fire Fighting Procedures Smother			
Unusual Fire and Explosion Hazards None			

